

UNITED STATES PATENT APPLICATION
FOR
RACK MOUNT SERVER WITH TILTABLE DISPLAY

INVENTOR:
MONTE J. RHOADS

PREPARED BY:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, LLP
12400 WILSHIRE BLVD.
SEVENTH FLOOR
LOS ANGELES, CA 90025-1030
(503) 684-6200

EXPRESS MAIL No. EL034435770US

RACK MOUNT SERVER WITH TILTABLE DISPLAY

FIELD OF THE INVENTION

The present invention relates to adjustable displays for rack mount devices, such as 1U/2U rack mount servers, wherein the rack mount devices have a tiltably attached display to allow for better viewing angles.

BACKGROUND OF THE INVENTION

Rack mount devices, such as 1U/2U rack mount servers, are typically stacked on mounts to allow efficient use of space. Rack mounted devices are very common and are stacked vertically in mounts in a manner known to those skilled in the art. Referring to **FIGURE 1**, a rack mount device **100**, having a front portion **110**, includes a display device on a user interface **120**. The display device typically has a flat panel LCD mounted on the front of its enclosure with the viewing screen parallel to the plane of the front of the device. When many rack mount devices are mounted on some larger racks the ability to view the display screen is lessened for devices mounted on the top or bottom of these racks. For example, because the screen is mounted parallel to the front face of the rack mount device, it is best seen from an ideal viewing angle directly in front of the screen where the view is both perpendicular to and centered on the viewing screen. This creates the viewing problem in the prior art where the devices above or below eye level are difficult to read due to the viewing angle. Most rack mount devices with displays suffer from similar shortcomings.

One solution to the viewability problem is to have a display with an adjustable brightness. This allows the viewer to adjust the harder to view screens on a higher setting to allow more visibility for poor viewing angles. However, this solution suffers from significant disadvantages. First, typical displays are LCDs which have a maximum viewing angle. Adjusting the intensity of the display only works if the viewer is still within this viewing range. This can be a disadvantage, for example, when the devices mounted near the top or bottom of the rack are outside of the viewing range.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings in which like reference numerals refer to similar elements.

Figure 1 is a side view of the prior art rack mount device with a LCD parallel to the plane of the front panel of the device.

Figure 2 is a side view of one embodiment of a rack mount device having a display with an adjustable viewing angle.

Figure 3 is a side view of one embodiment of a rack mount device having a display tiltably attached by a ball and socket joint allowing multiple degrees of freedom for adjustment.

Figure 4 is a side view of one embodiment of a rack mount device with the display attached by a single hinge attachment allowing one axis for rotation.

Figure 5A is a top view of one embodiment of a rack mount device with a double hinge attachment allowing two axes of rotation for the display screen.

Figure 5B is a side view of one embodiment of a rack mount device with a double hinge attachment allowing two axes of rotation for the display screen.

Figure 6 is a front view showing one embodiment of an adjustment mechanism to secure the screen from inadvertent adjustment.

Figure 7 is a side view showing one embodiment of an indexed attachment allowing the screen to be adjusted to discrete positions.

DETAILED DESCRIPTION

Rack mount devices with adjustable displays are described. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the invention. It will be apparent, however, to one skilled in the art that the invention can be practiced without these specific details. In other instances structures and devices are shown in block diagram form in order to avoid obscuring the invention.

Reference in the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

The rack mount devices with tiltably adjustable displays described herein provide a wider optimum viewing angle for rack mount devices than those of the prior art. The devices described herein as rack mount devices or as rack mount servers can also be any of numerous other types of appliances, including but not limited to, such as a hub, a router, a switch, an amplifier, a piece of audio or video editing or recording or playback equipment. The display devices in rack mount devices are generally flat panel LCDs but may also be but not limited to any LCD, an LED, and a CRT, or any other display known to those skilled in the art.

The adjustable display device may be connected to the rack mount server or rack mount device by a movable coupling. The movable coupling can be any of numerous connections, for example, a single-hinge joint, a double-hinge joint, a multiple-hinge joint, a ball and-socket-joint, two sliding surfaces constrained to contact with each other, or any combination of these, or any other connection known to those skilled in the art. In another embodiment the movable coupling can be indexed to allow incremental adjustment through discrete steps.

In one embodiment the display device **120** can be tiltably attached to the front **110** of the rack mount device **100**. Referring to the drawings more particularly by reference numbers, **FIGURE 2** shows one embodiment. In this embodiment the tiltably attached

display is coupled with the rack mount device by the movable coupling. This embodiment illustrates a range of motion **A**, which the display can adjust through that allows a wide range of optimum viewing.

Another embodiment, as shown in **FIGURE 3**, provides that the movable coupling of the display device **120** may be a ball and socket joint **130**. The ball and socket joint **130** may movably couple the display with the front **110** of the rack mount device or rack mount server **100** and allow multiple degrees of freedom of movement for the display.

In another embodiment, as shown in **FIGURE 4**, provides that the movable coupling of the display device **120** may be a single hinge with one axis of rotation **140**. The single hinge **140** may mount the display with the front **110** of the rack mount device or rack mount server **100** and allow the display to adjust about one axis. In the embodiment shown in **FIGURE 4** this axis is horizontal to allow for the viewing range to adjust vertically. Other embodiments allow the viewing range to be adjusted horizontally or along any angle ranging from the horizontal to the vertical.

Another embodiment, as shown in **FIGURE 5**, for example, provides that the movable coupling may be a double hinge **150** with two axis of rotation that are perpendicular and which allow two degrees of freedom of movement of the display device **120**. The display device can be coupled with the rack mount server or rack mount device through the movable coupling. **FIGURE 5A** and **FIGURE 5B** are top and side views of the embodiment comprising two hinges for the movable coupling.

Referring to **FIGURE 6**, one embodiment can include a securing mechanism **160** such as a tightening screw in order to secure the display device from adjustment. In this embodiment the screw is configured that when it is tightened it secures the display mechanism from movement.

Referring to **FIGURE 7**, another embodiment can include an indexed movable coupling. The indexed movable coupling allows incremental adjustment through discrete positions **170**. For example, the indexing may be a series of tabs that partially secures the display from movement. This embodiment would allow a plurality of semi-fixed positions that the display can adjust to.

Referring to **FIGURE 8**, an embodiment may be a rack mount server, or other computing system, comprising the tiltably attached display. **Figure 8** is a block diagram of one embodiment of a computer system. The computer system illustrated in **Figure 8** is intended to represent a range of computer systems. Alternative computer systems can include more, fewer and/or different components.

Computer system 800 includes bus 801 or other communication device to communicate information, and processor 802 coupled to bus 801 to process information. While computer system 800 is illustrated with a single processor, computer system 800 can include multiple processors and/or co-processors. Computer system 800 further includes random access memory (RAM) or other dynamic storage device 804 (referred to as main memory), coupled to bus 801 to store information and instructions to be executed by processor 802. Main memory 804 also can be used to store temporary variables or other intermediate information during execution of instructions by processor 802.

Computer system 800 also includes read only memory (ROM) and/or other static storage device 806 coupled to bus 801 to store static information and instructions for processor 802. Data storage device 807 is coupled to bus 801 to store information and instructions. Data storage device 807 such as a magnetic disk or optical disc and corresponding drive can be coupled to computer system 800.

Computer system 800 can also be coupled via bus 801 to display device 821, such as a cathode ray tube (CRT) or liquid crystal display (LCD), to display information to a computer user. In one embodiment the display device is tiltably attached to allow a wider viewing angle. Alphanumeric input device 822, including alphanumeric and other keys, is typically coupled to bus 801 to communicate information and command selections to processor 802. Another type of user input device is cursor control 823, such as a mouse, a trackball, or cursor direction keys to communicate direction information and command selections to processor 802 and to control cursor movement on display 821. Computer system 800 further includes network interface 830 to provide access to a network, such as a local area network.

Instructions are provided to memory from a storage device, such as magnetic disk, a read-only memory (ROM) integrated circuit, CD-ROM, DVD, via a remote connection (e.g., over a network via network interface 830) that is either wired or wireless, etc. In

alternative embodiments, hard-wired circuitry can be used in place of or in combination with software instructions to implement the present invention. Thus, the present invention is not limited to any specific combination of hardware circuitry and software instructions.

A machine-accessible medium includes any mechanism that provides (i.e., stores and/or transmits) information in a form readable by a machine (e.g., a computer). For example, a machine-accessible medium includes read only memory (ROM); random access memory (RAM); magnetic disk storage media; optical storage media; flash memory devices; electrical, optical, acoustical or other form of propagated signals (e.g., carrier waves, infrared signals, digital signals); etc.

In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes can be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000